

XOANONS® Silicon free defoamer

Model number

XOANONS®WE-D955

Composition

Organic silicon free foam destroying polymer solution

Specifications

Model number	Appearance	Solvent	Density g/ml (25±1 °C)	Viscosity(s) (25±0.2 °C)	Content(%) (140°C 2h)
XOANONS® WE-D955	Transparent to slight yellowish clear liquid	Butyl acetate	0.86-0.90	8-20 (T-4 viscometer)	20±3

Application system

Solvent based coating/paint Ink UV Cure

Addition

Model number	Addition to total formulation (%)
XOANONS®WE-D955	0.1-0.3

Incorporation

Should be added to the mill base for improve the foam-inhibition, deaeration and defoaming speed of the system

Property and advantage

Model number	Property and advantage
XOANONS®WE-D955	Excellent foam-inhibition and deaeration ability without side-effect. Have a good ability of compatibility in varnish. Be suitable for wood coating, industry coating, and UV Cure system.

Package

25KG/180KG

The container should be closed tightly before completely used up

Storage

Should store in cool and dry place

Can keep intact 24 months in original package.

This information is given to the best of our knowledge. Because of the multitude of formulations, production, and application conditions, all the above mentioned statements have to be adjusted to the circumstances of the processor.